

BattMan Lite



Product code: 70405060

Battery monitor, 12/24 V DC with large, splash proof display (IP65) and power bar.

An affordable battery monitor that does exactly that: providing critical information about the status of your battery bank under all circumstances. Moreover it will warn you when your battery bank is empty.

Specifications

General specifications

Number of battery outlets	2; service (fully), starter (voltage)
Display/read-out	voltage, current, amp-hours, battery capacity in %
Languages on display	universal
Built-in depth	72.5 mm
	2.9 inch
Dimensions	Ø 64 mm, depth 79 mm
Dimensions shunt, hwxwd	87 x 45 x 35 mm
	3.4 x 1.8 x 1.4 inch
Weight	0.15 kg
	0.3 lb

Technical specifications

Max. Ah capacity	9999 Ah
Supply voltage	9-35 V
Voltage range	0-35 V
Current consumption (backlight off)	8 mA/12 V, 6 mA/24 V
Current consumption (backlight on)	30 mA/12 V, 18 mA/24 V
Voltage resolution	0.1 V
Voltage accuracy	± 0.3%
Shunt specification	500 A/50 mV (service set)
Current measurement range	0-500 A
Current accuracy	± 0,4 %
Battery alarm contact	yes, potential free
Remaining time indication	no
Historical data	no
MasterBus compatible	no
Connection cable (6-wire) necessary	yes
Modular cable necessary	no