

# MasterShunt + EasyView 5



Product code: 77020110 + 77010310

The MasterShunt in combination with an EasyView 5 panel is the most advanced battery monitor you can find. Touchscreen control of all functions.

MasterBus integrated battery monitor collecting detailed information on the status of your batteries. The EasyView 5 remote panel with touchscreen control provides information on the charge process as well as other system information.

# Specifications

## General specifications

Number of battery outlets	one battery set per MasterShunt
Display/read-out	voltage, current, amp-hours, time remaining, battery capacity in %, inverter & charger operation, Power Sharing, special battery status events
Languages on display	English, Dutch, French, Spanish, German, Danish, Finnish, Norwegian, Italian, Swedish
Dimensions, hxxxd	113 x 127 x 43 mm 4.4 x 5.0 x 1.7 inch
Dimensions shunt, hxxxd	150 x 150 x 65 mm 5.9 x 5.9 x 2.6 inch
Weight	1 kg 2.2 lb

## Technical specifications

Max. Ah capacity	9999 Ah
Supply voltage	8-60 V
Voltage range	0-60 V
Current consumption (backlight off)	32 mA/12 V, 17 mA/24 V
Current consumption (backlight on)	100 mA/12 V, 50 mA/24 V
Voltage resolution	0.1 V
Voltage accuracy	± 0.6 %
Shunt specification	digital shunt
Current measurement range	0-500 A
Current accuracy	± 0.8 %
Battery alarm contact	yes, via MasterBus alarm interface
Remaining time indication	yes
Historical data	yes
MasterBus compatible	yes
Connection cable (6-wire) necessary	no
Modular cable necessary	MasterBus cable included