

EasyCharge Portable 4.3A



Product code: 43510400

Waterproof portable battery charger

For people on the move, the EasyCharge portable battery charger offers a rugged solution that can be used on the boat, car, motorcycle, and camper van. With a rugged, ergonomic construction, and waterproof to IP65 standard, the portable charger has an intuitive control panel and a universal input (120-230 V) for total worldwide freedom.

Users can quickly select between 6 V (ideal for toys, classic cars and motorcycles) and 12 V operation. The unit includes 1.8m of DC cable that connects to either a 61cm lead with ring terminals, or a 61cm lead with alligator clips, for easy installation and a variety of applications; both leads are included in the package.

Specifications

General specifications

| | |
|--|---|
| Total charge current | 4.3 A |
| Recommended battery capacity: maintain | 14 to 120 Ah |
| Recommended battery capacity: charge | 14 to 90 Ah |
| Nominal input voltage | 120/230 V (90-265 V), 50/60 Hz |
| AC connection | 1.8 m (6 ft) cable + Euro plug (CEE7/16) |
| DC connection | ring and alligator clip connections, with integrated fuse |
| Galvanic isolation | yes |
| Dimensions, hxxwxd | 161 x 72 x 43.7 mm |
| | 6.3 x 2.8 x 1.7 inch |
| Weight | 0.9 kg |
| | 2.0 lb |
| Compliance | CE, ABYC |
| Optional | also available with UK plug, product code 43510402 |

Technical specifications

| | |
|-----------------------------------|--|
| Charge characteristic | IUoUo, automatic 3-step+ for Gel/AGM/flooded/Lithium Ion |
| Temperature range (ambient temp.) | -20 °C to 40 °C |
| | -4 to 104 °F |
| Protection degree | IP65 |
| Protections | short circuit, reverse polarity, over voltage, current limited, over temperature |
| MasterBus compatible | no |