IVET-D 16A 3.5kW multi tap

	1		-
	<u></u>	1	
		-	12
			12
			121
			121
© IVET-D 16 / 3	.5 MT		
IVET-D 16 / 3. Scheidingstransformator Isolation transformer Isolations Transformator Transformateur disolation	.5 MT	٩	
IVET-D 16 / 3. Scheidingstransformator Isolation Transformator		٩	
IVET-D 16 / 3. Scheidingstransformator Isolation transformetor Isolations Transformator Transformateur disolation Power rating 3.5KVA / IAA			

Product code: 86060351



The Mastervolt IVET-D toroidal isolation transformer is supplied as a 3.5 kW/16 A version for 220-240 V. Multi-tap version for both 230V/50Hz and 120V/60Hz shore voltage.

Supplied in a compact robust box with a double pole circuit breaker on the AC outlet, which guarantees optimum safety. The build-in Soft Start suppresses the inrush current from the transformer and prevents the shore power fuse from blowing.

The convenient connection compartment features professional connection terminals. All Mastervolt isolation transformers comply with the CE and ABYC (US norm) guidelines.



Specifications

General specifications

Output voltage (± 5 %) Output frequency range Input voltage range Input frequency range Nominal input current (230 V) Efficiency Power Dimensions, hxwxd

Weight

Technical specifications

Technology Earth leakage protection No-load power consumption Temperature range (ambient temp.)

Cooling Switch off at Relative humidity Protection degree Switch off behaviour breaker Soft start MasterBus compatible 220-240 V / adjustable 110-120 V 45-65 Hz 220-240 V / adjustable 110-120 V 45-65 Hz 16 A > 93 % 3500 W 407 x 295 x 220 mm 16.0 x 11.6 x 8.7 inch 23 kg 50.7 lb

torroidal no < 10 W 0-40 °C, derating power > 40 °C 32 to 32 °F natural cooling, forced cooling > 80 °C 120 °C max. 95% IP23 B-characteristic yes no

