

# MLI-E 12/1200



Product code: 66011200

The Mastervolt MLI-E Lithium Ion battery closes the gap between the very compact MLS battery and the successful high capacity MLI Ultra series. The MLI-E is ideal for applications where long lifespan, light weight, fast charging and compactness are key. Its practical form factor makes the MLI-E perfectly suitable for mobile applications.

### Compact, maintenance free power, ideal for mobile applications

Lithium Ion has many advantages over lead-acid. The MLI-E saves up to 70 % in space and weight, recharges in less than an hour, and deep cycles 5.000 times easily, which is up to 10 times longer than lead-acid batteries. The MLI-E can replace a 180-200 Ah lead-acid battery. Also, for the MLI-E the extremely safe Lithium Ion (LiFePO4) chemistry is used.

No external safety relay is needed. The MLI-E is protected against overcharging, deep discharging and overheating and comes with an integrated electronic safety switch. With its waterproof plastic case, the MLI-E is a straight-forward replacement for most lead-acid batteries.

LED indicators inform you about the actual status of your battery. Of course, the MLI-E is provided with integrated battery monitoring, including information about state of charge and time remaining. For optimal integration in both mobile and maritime power systems, both NMEA2000 / CZone and CANopen protocols are supported. Needless to say, the MLI-E fits perfectly into a MasterBus system, when combined with our system monitor EasyView 5\*. And last but not least: hands-on monitoring is available, using Bluetooth and a mobile app.

### Features

- Very long lifespan, maintenance free.
- Fast charging and discharging, fully charged within an hour.
- Straight-forward replacement for most existing lead-acid batteries (EqPb: 200 Ah).
- Compact, practical size.
- Extremely safe Lithium Ion chemistry (LiFePO4).
- Integrated safety switch for quick and easy installation.
- High performance even under harsh conditions.
- High efficiency and low self-discharge.
- Integrated battery monitoring for reliable battery status information.
- System integration via NMEA2000 / CZone, CANopen or MasterBus (via EasyView 5\*).
- Monitoring via Bluetooth app possible.

### Applications

Its size, weight, tough waterproof case and resistance to shocks makes the MLI-E ideal for mobile applications. Other applications range from marine, infrastructure, off-grid to industrial applications.

\* Max. two MLI-E batteries per EasyView 5. Refer to manual for details.

# Specifications

## Communication & monitoring

Communication

LED indicators, CANopen, CZone/NMEA 2000 (through drop cable CZone/MasterBus, product code 77046000), MasterBus (through EasyView 5\*, product code 77010310), Bluetooth (via mobile app)

## General specifications

Nominal battery voltage	13.2 V
Nominal battery capacity	90 Ah
Nominal battery energy capacity	1200
Cycle life	
Max. charge current	90 A (1 C)
Continuous discharge current	200 A (2.2 C)
Peak discharge current	350 A (3,8 C) for 30 s
Battery monitoring	integrated
Battery terminals	automotive or M8 hexagon
Mounting position	mountable in multiple orientations, suitable for LN5 fastening brackets
Battery standard	Group 49, H8
Battery designation	IEC 62620: IFpR19/67[60p4s]M/-10+60/90 - IEC 61960: 4IFpR19/67-60
Max. outer dimensions (incl. terminals/grip handles), lxxwxh	353 x 175 x 190 mm 13.9 x 6.9 x 7.5 inch
Weight	12.5 kg 27.6 lb
Delivered with	2x automotive battery pole, 2x M8 bolt, hexagon tool, USB stick (with manual)

## Technical specifications

Battery chemistry	Lithium Iron Phosphate (LiFePO4)
Temperature range (ambient temp.)	discharge -20 °C to 60 °C, derating < 0 °C and > 45 °C / charge -10 °C to 45 °C, derating < 0 °C and > 45 °C 32 to 32 °F
Protection degree	IP51
Parallel connection	yes, unlimited
Series connection	no
Protections	over voltage, under voltage, over-temperature
Safety disconnect	automatic, integrated