

EasyView 5



Product code: 77010310

Waterproof System Monitor with 'daylight readable' display and intuitive

touchscreen

Controlling your Mastervolt system has never been easier. The EasyView 5 features a sharp, waterproof display which is clearly readable in daylight. Thanks to the colour touchscreen and multi-language menu, the display is a pleasure to operate. Easily customizable favourite pages show all relevant system information at a glance.

Features

- Water proof, 'daylight readable' colour display.
- Intuitive touch control.
- Customizable favourite pages.
- Log book for warnings and alarms.
- Buzzer and Home button.
- Easy mounting: front mount, wall mount or retrofit.
- MasterBus powered, or 12/24 V input.
- Easy updating through MasterBus and USB.
- CE, E-Mark certified.

Applications

The EasyView 5 completes any MasterBus system. With its handy functionality and compact size, the EasyView is ideal for yachts, vehicles and stationary systems. Applicable in various markets such as marine, mobile (recreational and professional), infrastructure, offshore, off grid and industrial. The possibilities are endless!

Some examples of the many possibilities:



Customize Favourites.

Customize favourite pages to meet your specific needs for information and control, to show information in the most convenient way.



Adjust Parameters.

Use the EasyView 5 to adjust frequently used settings, like the shore fuse or to switch on your inverter.



Modify System Settings.

In the system page you will find every possible system setting.



Alarms and Logs.

No surprises! The EasyView 5 helps to keep your system in top condition by assisting you with alerts. Logging of the alarms provides valuable insight in the operation of your system.

Specifications

General specifications

Power supply	MasterBus powered, or 12/24 V input (9 - 32 V)
Resolution	480 x 272 pixels
Colour depth	16 bits
Display/read-out	4.3 inch high contrast display with capacitive touch control
Languages on display	ENG, NL, DE, SP, IT, FRA, FIN, SWE, DEN, NOR
Mounting	panel mounting, flush mounting, MasterView Easy retrofit
Alarms	buzzer integrated
Dimensions, hxxxd	113 x 127 x 43 mm
	4.4 x 5.0 x 1.7 inch
Weight	0.315 kg
	0.7 lb
Delivered with	UV protection cover, wall mount casing, MasterBus cable

Technical specifications

MasterBus connection	yes
Power consumption	< 160 mW (idle mode)
Connections	2x MasterBus, USB, 12/24 V
Temperature range (ambient temp.)	-20 °C to 70 °C
	-4 to 158 °F
Protection degree	IP67; waterproof front