

# Masterswitch 25 kW (230 V)



Product code: 55003500

- Two AC inputs, for example grid power and generator.
- One outlet to AC power group.
- Automatic switching.
- Power transfer up to 25 kW, input/output from 20 to 125 A.

The Masterswitch Fuses version includes circuit breakers.

# Specifications

## General specifications

Nominal input voltage	230 V (50/60 Hz)
Input voltage range	200-250 V
Number of inputs	2
Number of outputs	1
Dimensions, hwxwd	291 x 241 x 168 mm 11.5 x 9.5 x 6.6 inch
Weight	3.8 kg 8.4 lb

## Technical specifications

Connection for remote control	no
LED indication on enclosure	no
Nominal input current generator	125 A
Nominal input current grid	125 A
Generator input switch	no
Time delay generator input	0-10 sec (adjustable)
Nominal current power output	125 A
Automatic circuit breakers	no, system dependent
Power consumption (AC all inputs)	26 W
Power consumption (only inverter power)	0 W
Transfer time	switch on 12-22 ms / switch off 4-19 ms
Temperature range (specified)	-5 °C to 60 °C 23 to 140 °F
Temperature range (ambient temp.)	-25 °C to 70 °C -13 to 158 °F
Temperature range (storage/non operating)	-60 °C to 80 °C -76 to 176 °F
Relative humidity	max. 95%, non condensing
Frequency watch	no
Cable size	4-50 mm <sup>2</sup> /AWG 10-1/0
Protection degree	IP55
MasterBus compatible	no